



*experience,
trust, service*

800-BLAST-IT
www.marcousa.com

Davenport, IA • Houston, TX • Shreveport, LA • Savannah, GA • Harrisburg, PA

Autofax #00093311
page 1 of 2

Updated: 08/20/03

OSHA STANDARD 1910.134

- ▶ **1910.134(i)**
Breathing air quality and use. This paragraph requires the employer to provide employees using atmosphere-supplying respirators (*supplied-air and SCBA*) with breathing gases of high purity.
- ▶ **1910.134(i)(1)**
The employer shall ensure that compressed air, compressed oxygen, liquid air, and liquid oxygen used for respiration accords with the following specifications:
 - ▶ **1910.134(i)(1)(i)**
Compressed and liquid oxygen shall meet the United States Pharmacopoeia requirements for medical or breathing oxygen; and
 - ▶ **1910.134(i)(1)(ii)**
Compressed breathing air shall meet at least the requirements for Grade D breathing air described in ANSI/Compressed Gas Association Commodity Specification for Air, G-7.1-1989, to include:
 - ▶ **1910.134(i)(1)(ii)(A)**
Oxygen content (v/v) of 19.5-23.5%;
 - ▶ **1910.134(i)(1)(ii)(B)**
Hydrocarbon (*condensed*) content of 5 milligrams per cubic meter of air or less;
 - ▶ **1910.134(i)(1)(ii)(C)**
Carbon monoxide (CO) content of 10 ppm or less;
 - ▶ **1910.134(i)(1)(ii)(D)**
Carbon dioxide content of 1,000 ppm or less; and
 - ▶ **1910.134(i)(1)(ii)(E)**
Lack of noticeable odor.
 - ▶ **1910.134(i)(2)**
The employer shall ensure that compressed oxygen is not used in atmosphere-supplying respirators that have previously used compressed air.
 - ▶ **1910.134(i)(3)**
The employer shall ensure that oxygen concentrations greater than 23.5% are used only in equipment designed for oxygen service or distribution.
 - ▶ **1910.134(i)(4)**
The employer shall ensure that cylinders used to supply breathing air to respirators meet the following requirements:
 - ▶ **1910.134(i)(4)(i)**
Cylinders are tested and maintained as prescribed in the Shipping Container Specification Regulations of the Department of Transportation (*49 CFR part 173 and part 178*);
 - ▶ **1910.134(i)(4)(ii)**
Cylinders of purchased breathing air have a certificate of analysis from the supplier that the breathing air meets the requirements for Grade D breathing air; and

-
- ▶ **1910.134(i)(4)(iii)**
The moisture content in the cylinder does not exceed a dew point of -50 deg.F (-45.6 deg.C) at 1 atmosphere pressure.
 - ▶ **1910.134(i)(5)**
The employer shall ensure that compressors used to supply breathing air to respirators are constructed and situated so as to:
 - ▶ **1910.134(i)(5)(i)**
Prevent entry of contaminated air into the air-supply system;
 - ▶ **1910.134(i)(5)(ii)**
Minimize moisture content so that the dew point at 1 atmosphere pressure is 10 degrees F (5.56 deg.C) below the ambient temperature;
 - ▶ **1910.134(i)(5)(iii)**
Have suitable in-line air-purifying sorbent beds and filters to further ensure breathing air quality. Sorbent beds and filters shall be maintained and replaced or refurbished periodically following the manufacturer's instructions.
 - ▶ **1910.134(i)(5)(iv)**
Have a tag containing the most recent change date and the signature of the person authorized by the employer to perform the change. The tag shall be maintained at the compressor.
 - ▶ **1910.134(i)(6)**
For compressors that are not oil-lubricated, the employer shall ensure that carbon monoxide levels in the breathing air do not exceed 10 ppm.
 - ▶ **1910.134(i)(7)**
For oil-lubricated compressors, the employer shall use a high-temperature or carbon monoxide alarm, or both, to monitor carbon monoxide levels. If only high-temperature alarms are used, the air supply shall be monitored at intervals sufficient to prevent carbon monoxide in the breathing air from exceeding 10 ppm.
 - ▶ **1910.134(i)(8)**
The employer shall ensure that breathing air couplings are incompatible with outlets for nonrespirable work site air or other gas systems. No asphyxiating substance shall be introduced into breathing air lines.
 - ▶ **1910.134(i)(9)**
The employer shall use breathing gas containers marked in accordance with the NIOSH respirator certification standard, 42 CFR part 84.
 - ▶ **1910.134(j)**
Identification of filters, cartridges, and canisters. The employer shall ensure that all filters, cartridges and canisters used in the workplace are labeled and color coded with the NIOSH approval label and that the label is not removed and remains legible.
 - ▶ **1910.134(k)**
Training and information. This paragraph requires the employer to provide effective training to employees who are required to use respirators. The training must be comprehensive, understandable, and recur annually, and more often if necessary. This paragraph also requires the employer to provide the basic information on respirators in Appendix D of this section to employees who wear respirators when not required by this section or by the employer to do so.



For more information call:

800-BLAST-IT

Phone: 800-252-7848

Fax: 563-324-6258

e-mail: sales@marcouisa.com

www.marcousa.com

