



experience,
trust, service

800-BLAST-IT
www.marcousa.com

Dallas, TX • Davenport, IA • Harrisburg, PA • Houston, TX • New Orleans, LA • Savannah, GA

Autofax #00093723

page 1 of 4

Updated: 02/26/07

MSDS SHEET - STARBLAST

I. Chemical Product & Company Identification

Trade Names and Synonyms: Starblast, Starblast XL, Starblast Ultra
Manufacturer/Distributor: DuPont Titanium Technologies
Plant Location: 1007 Market Street
 Wilmington, DE 19898
Product Information Telephone Number: 800-441-9485 (Outside US 302-774-1000)
Transport Emergency Telephone Number: CHEMTREC: 800-424-9300 (Outside US 703-527-3887)
Medical Emergency Telephone Number: 800-441-3637 (Outside US 302-774-1000)

II. Composition & Ingredient Information

Ingredient	CAS #	% in Starblast	% in Starblast XL	% in Starblast Ultra
Staurolite	12182-56-8	86	90	85
Titanium Minerals		6	6	7
Quartz	14808-60-7	< 5	< 1	<5
Zircon	14940-68-2	3	2	3
Kyanite	1302-76-7	2	1	2

III. Hazards Identification

Potential Health Effects: Eye contact with the product may cause irritation with discomfort, tearing or blurring of vision.

The product, as shipped, does not pose an inhalation health hazard because it contains essentially no particles in the respirable size range. However, if during handling or use the particles are broken down to a size that can be inhaled, the dust may be harmful to the respiratory system. Individuals with pre-existing conditions of the lungs may have increased susceptibility to the toxicity of excessive exposures.

Staurolite Products contain trace quantities (<5%) of quartz. The predominant effect of overexposure to airborne respirable Quartz in humans is silicosis. Silicosis is a chronic disease characterized by formation of silica-containing scar tissue in the lungs with symptoms of coughing, dyspnea, wheezing and nonspecific respiratory ailments. Very high short exposures to Crystalline Silica may lead to fatality from gross overexposure.

Several recent epidemiology studies have shown that in addition to silicosis, there is limited evidence of an excess of lung cancer in occupations involving exposures mainly to Crystalline Silica, such as stone cutters and granite industry workers.

Staurolite Products contain trace quantities (less than or equal to 28 pCi/g) of naturally occurring radioactive uranium and thorium (less than or equal to 200 ppm total uranium and thorium or 0.02 % w/w) and (less than or equal to 28 pCi/g) radium. Naturally Occurring Radioactive Material, namely uranium, thorium and their decay products, is commonly referred to as "NORM".

The main radiological hazard from the product is internal exposure from small amounts of alpha particles given off by inhaled dust. Industrial hygiene practices aimed at control of airborne dust can lessen the potential for exposure. Overexposure by inhalation to inhaled dusts containing radioactive uranium, thorium and radium may cause lung cancer. Low level gamma radiation in proximity to bulk or bagged stockpiles of zircon may present a lesser, external exposure that can be managed by limiting close proximity for long time periods to large volumes of material.

Staurolite is exempt from Nuclear Regulatory Commission (NRC) regulations for source material per 10 CFR 40, since it falls under the definition of "unimportant quantity source material" containing less than 0.05% uranium or thorium. Some states may apply NRC type radiation protection standards for NORM above background levels, or may have NORM specific regulations. It is recommended that you consult and comply with current regulations.

With respect to dust exposure (8 hr/day TWA basis, 10 um aerodynamic, or about 5 um physical diameter particle size used for calculation purposes), evaluation and calculation of OSHA PEL's

(29 CFR 1910), ACGIH TLV's and NRC standards (10 CFR 20) for trace crystalline silica and trace radionuclides indicate that a level of approximately 4.3 mg/m³ of total dust (or 1.0 mg/m³ of respirable dust) will ensure that intake is less than the NRC public dose limit for radionuclides and less than OSHA and ACGIH limits for respirable and total quartz. Quartz is the most limiting of the trace components. If during handling or use the particles are broken down to finer particle sizes, lower levels of total dust would apply.

Carcinogenicity Information: The following components are listed by IARC, NTP, OSHA or ACGIH as carcinogens.

Material	IARC	NTP	OSHA	ACGIH
Quartz	1	X		A2

DuPont controls the following materials as carcinogens: Quartz.

IV. First Aid Measures

Inhalation: If inhaled, immediately remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Call a physician.

Skin Contact: The compound is not hazardous by skin contact, but removal of particles and cleansing the skin after use is advisable.

Eye Contact: In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Call a physician.

Ingestion: No specific intervention is indicated as the compound is not hazardous by ingestion. However, if symptoms occur, consult a physician.

V. Fire Fighting Measures

Flammable Properties:

Will not burn

Extinguishing Media:

As appropriate for combustibles in area

Fire Fighting Instructions:

None

VI. Accidental Release Measures

Safeguards (Personnel): NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

Accidental Release Measures: Sweep up spillage.

VII. Handling & Storage

Handling (Personnel): Avoid breathing dust. Wash thoroughly after handling. If handling respirable flour, use of gloves and washing before eating, drinking, applying cosmetics or smoking is advisable to minimize dust inhalation or ingestion from hands.

VIII. Exposure Controls & Personal Protection

Engineering Controls: Use sufficient ventilation to keep employee exposure below recommended limits.

If using this product as an abrasive blasting agent in confined areas, airborne dust levels should be controlled by physical enclosure of the abrasive blasting operation. The enclosure should be exhaust ventilated in accordance with 29 CFR 1910.94 Ventilation (a) Abrasive Blasting.

Personal Protective Equipment:

Eye/Face Protection: Wear safety glasses with side shields.

Respirator: A NIOSH approved air-purifying respirator with a type 100 (high efficiency) particulate cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air-purifying respirators is limited. Use a NIOSH approved positive pressure air-supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known or any other circumstances where air-purifying respirators may not provide adequate protection.

For abrasive blasting use a type CE abrasive-blast, supplied-air respirator covering head, neck and shoulders to provide protection from rebound abrasive per 29 CFR 1910.94 (a)(5).

Protective Clothing: Wear impervious clothing, such as gloves, apron, boots or whole bodysuit, as appropriate.

Exposure Guidelines

Applicable Exposure Limits:

QUARTZ

PEL (OSHA) Total dust, (30 mg/m³ / % SiO₂ + 2)
Respirable dust, (10 mg/m³ / % SiO₂ + 2) as 8 Hr TWA's

TLV (ACGIH): 0.05 mg/m³, respirable dust, 8 Hr. TWA, A2
Or see: Christobalite [14464-46-1], Silica, Fused [60676-86-0], Tridymite [15468-32-2], Tripoli [1317-95-9]

AEL* (DuPont): 0.1 mg/m³, 8 Hr. TWA, respirable dust

ZIRCON

PEL (OSHA): 5 mg/m³, 8 Hr. TWA, as Zr

TLV (ACGIH): 5 mg/m³, 8 Hr. TWA, as Zr, A4
STEL 10 mg/m³, as Zr, A4

AEL* (DuPont): None Established

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

IX. Physical & Chemical Properties

Vapor Pressure: Not volatile
Vapor Density: Not volatile
Melting Point: 1,370° C (2,500° F)
Evaporation Rate (Butyl Acetate = 1): Not volatile
Solubility in Water: Insoluble
Odor: Odorless
Form: Solid, free-flowing sand
Color: Reddish brown
Specific Gravity: 3.7

X. Stability & Reactivity

Chemical Stability: Stable
Incompatibility with other materials: None reasonably foreseeable
Decomposition: Will not occur
Polymerization: Will not occur

XI. Toxicological Information

Animal Data: Quartz: Oral ALD: > 11,000 mg/kg in male rats

Quartz is not a skin irritant or a skin sensitizer in animals but is a mild eye irritant. Single doses of 50 mg Quartz administered by intratracheal instillation have resulted in pulmonary fibrosis at 60 and 120 days post exposure in rats. Repeated and chronic exposures as low as 0.7 mg instillation and 12 mg/m³ by inhalation resulted in pulmonary fibrosis, inflammation, edema and emphysema in animals exposed to Quartz. Lung tumors were also observed in rats exposed for up to two years by inhalation to 12.4 or 51.6 mg/m³ Quartz. Lung tumors were observed in rats exposed to Quartz by intratracheal instillation. Silica was positive in mammalian cell cultures for cell transformation and chromosomal effects. It was negative in cell culture assays for gene mutation in bacteria and DNA damage in mammalian cells and in a whole animal assay for chromosomal effects. No animal test reports are available to define developmental, or reproductive toxicity.

XII. Disposal Considerations

Waste Disposal: Treatment, storage, transportation and disposal must be in accordance with applicable Federal, State/Provincial and Local regulations.

If approved, may be transferred to a land disposal site.

NOTE: Some states have, or are developing, new regulations for disposal of waste containing Naturally Occurring Radioactive Materials (NORM) above background levels. It is recommended that you consult and comply with current regulations.

XIII. Transportation Information

Shipping Containers: Hopper cars, hopper trucks, bags and semi-bulk bags

Staurolite Products are not regulated as a hazardous material by DOT or IMO.

XIV. Regulatory Information

U.S. Federal Regulations

TSCA Inventory Status: Reported/Included.

TITLE III HAZARD CLASSIFICATIONS SECTIONS 311, 312

Acute: No **Chronic:** Yes
Fire: No **Reactivity:** No
Pressure: No

LISTS:

SARA Extremely Hazardous Substance: No **CERCLA Hazardous Material:** No
SARA Toxic Chemical: No

Staurolite is exempt from Nuclear Regulatory Commission (NRC) regulations for source material per 10 CRF 40, since it falls under the definition of "unimportant quantity source material" containing less than 0.05% uranium or thorium.

CANADIAN WHMIS CLASSIFICATION: D-2A

XV. Other Information

**NFPA, NPCA-HMIS
NPCA-HMIS Rating**

Health: 1 **Health:** x (Chronic Health Effects)
Flammability: 0 **Reactivity:** 0

Personal Protection rating to be supplied by user depending on use conditions.

Additional Information: For further information, see DuPont Staurolite Sands Data Sheet.

Please see www.titanium.dupont.com for the latest version of this MSDS.

WARNING! This product contains quartz and radionuclides which is known to the state of California to cause cancer.

The data in the Material Safety Data Sheet relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.

This information is based upon technical information believed to be reliable. It is subject to revision as additional knowledge and experience is gained.

XVI. Silicosis Warning

⚠ DANGER Breathing dust containing silica will cause silicosis, a fatal lung disease. Breathing dust during blasting operations will cause asbestosis, lead poisoning and/or other serious or fatal diseases. A NIOSH-approved, well-maintained, supplied-air abrasive blasting respirator must be used by anyone blasting, anyone handling or using the abrasive and anyone in the area of the dust. Harmful dust containing toxic material from abrasives or surfaces being blasted can remain suspended in the air for long periods of time after blasting has ceased. Failure to avoid the above danger will result in death or serious injury.

⚠ DANGER You must comply with all OSHA, local, City, State, Province, Country and jurisdiction regulations, ordinances and standards, related to your particular work area and environment. Keep unprotected individuals out of the work area. Failure to avoid the above danger will result in death or serious injury.



For more information call:

800-BLAST-IT

Phone: 800-252-7848
Fax: 563-324-6258
e-mail: sales@marcouisa.com
www.marcouisa.com

DISCLAIMER: The information in this MSDS was obtained from sources, which we believe are reliable. However, the information is provided without any representation or warranty, expressed or implied, regarding accuracy. These conditions or methods of handling, storage use and disposal of the product are beyond our control and may be beyond our knowledge. For this and other reasons, we do not assume responsibility and expressly disclaim liability for loss, damage or expense arising out of or in any way connected with the handling, storage, use or disposal of the product. Customers/users of silica must comply with all applicable health and safety laws, regulations and orders, including the OSHA Hazardous Communication Standard.

